

Hi-Cam

Be Safe, Drive Smart.

Because your safety is all we care about



www.hi-cam.com.tw

No.26-13-1, Fongle Road, Beitun District, Taichung City, Taiwan
hi-cam@hi-cam.com.tw TEL: +886-4-2422-3369 FAX: +886-4-24224360

Hi-Cam

More things you'll love to do with HI-CAM TPMS...



Smart Alert Feature



Low Power Consumption



Intuitive User Experience



Safe Driving Interface



Patented Valve Design



High Signal Quality and Strength



Model

Car



Truck



Motorcycle



Senor and Transmitter Specifications

Battery life	More than 5 years (normally, driving the car continuously for 3 hours per day)	More than 5 years (normally, driving the car continuously for 4 hours per day)	Coming soon
Storage temperature	-40°C to 85°C / 125°C	-40°C to 125°C	
Operating temperature	-40°C to 85°C / 125°C	-40°C to 125°C	
Operating humidity	95%	95%	
Operating frequency	315MHz / 433.92MHz	315MHz / 433.92MHz	
Pressure monitoring range	0~130psi (900 kpa)	0~217psi (1500 kpa)	
Pressure reading accuracy	At normal condition ± 1psi at normal pressure range	At normal condition ± 3psi at normal pressure range	
Temperature reading accuracy	± 4°C in normal environmental condition	± 4°C in normal environmental condition	
Sensor Weight	47.5g (incldues valve 16.5g)	88g (incldues valve 56g)	

Receiver Specifications

Display	2.8" Color LCD
Operating voltage	5V DC
Operating current	<250 mA
Operating temperature	-25°C to 75°C
Storage temperature	-30°C to 80 °C



*Option: Built-in Bluetooth / Multi-system integration